

SCF

4.5Ø x 14.5 mm

Fast-Acting Fuse



Agency Approvals

| Agency | Ampere Rating |
|--|---------------|
| Certified products for U.S. and Canada | 100mA - 8A |

Interrupting Rating

| | |
|----------|---------------------------|
| 1A - 8A: | 10,000 amperes at 125V AC |
| 1A - 8A: | 200 amperes at 250V AC |
| 1A - 8A: | 100 amperes at 350V AC |

Product Characteristics

| | |
|-----------------------|--|
| Operating Temperature | -55 °C to 125 °C |
| Material | Body: Ceramic / Caps: Nickel Plated Brass |


Electrical Characteristics

| Ampere Rating | Opening Time | | |
|---------------|--------------|---------|-------|
| | 1 In | 1.35 In | 2 In |
| | MIN | MAX | MAX |
| 1A - 8A | 4 hr | 1 hr | 5 sec |

Packaging

| Packaging Option | Quantity |
|------------------|-----------------|
| Bulk | 2,000 pcs / box |

Mechanical Dimensions (mm)



SCF-A

4.5Ø x 14.5 mm

Fast-Acting Fuse



Agency Approvals

| Agency | Ampere Rating |
|--|---------------|
| Certified products for U.S. and Canada | 100mA - 8A |

Interrupting Rating

| | |
|----------|---------------------------|
| 1A - 8A: | 10,000 amperes at 125V AC |
| 1A - 8A: | 200 amperes at 250V AC |
| 1A - 8A: | 100 amperes at 350V AC |

Product Characteristics

| | |
|-----------------------|---|
| Operating Temperature | -55 °C to 125 °C |
| Material | Body: Ceramic / Caps: Nickel Plated Brass |
| Leads Wire | Ø0.63 mm 7A and less. Ø1.0 mm for rating above 8A. |

Electrical Characteristics

| Ampere Rating | Opening Time | | |
|---------------|--------------|---------|-------|
| | 1 In | 1.35 In | 2 In |
| | MIN | MAX | MAX |
| 1A - 8A | 4 hr | 1 hr | 5 sec |

Packaging

| Packaging Option | Quantity |
|----------------------|-----------------|
| Bulk | 500 pcs / box |
| On Axial Tape & Reel | 1,000 pcs / box |

Mechanical Dimensions (mm)

